

**SAFETY DATA SHEET**

Safety Data Sheet



Date Prepared : 06/04/2014

SDS No : 131830

Date Revised : 09/28/2015

Revision No : 1

**Gelcoat, White with Wax, PL-807-1****1. PRODUCT AND COMPANY IDENTIFICATION****PRODUCT NAME:** Gelcoat, White with Wax, PL-807-1**PRODUCT CODE:** 131830**MANUFACTURER**

Fiberglass Coatings Inc.  
4301A 34th Street North  
St. Petersburg, FL 33714

**Customer Service:** (800) 272-7890**E-Mail:** www.fgci.com**Emergency Contact:** Chem-Tel**Emergency Phone:** (800) 255-3924**24 HR. EMERGENCY TELEPHONE NUMBERS**

Chem-Tel (800) 255-3924

**2. HAZARDS IDENTIFICATION****GHS CLASSIFICATIONS****Health:**

Skin Irritation, Category 2  
Skin Sensitization, Category 1  
Carcinogenicity, Category 1B  
Reproductive Toxicity, Category 2

**Environmental:**

Aquatic Toxicity, Category 2

**Physical:**

Flammable Liquids, Category 3

**GHS LABEL**

Flame

Health  
hazardExclamation  
mark**SIGNAL WORD:** DANGER**HAZARD STATEMENTS**

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H333: May be harmful if inhaled.

H361: Suspected of damaging fertility or the unborn child

H351: May cause cancer  
 H372: Causes damage to organs through prolonged or repeated exposure  
 H317: May cause an allergic skin reaction.  
 H335: May cause respiratory irritation.

## PRECAUTIONARY STATEMENT(S)

### Prevention:

P202: Do not handle until all safety precautions have been read and understood.  
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P223: Do not allow contact with water.  
 P240: Ground and bond container and receiving equipment.  
 P241: Use explosion-proof equipment.  
 P280: Wear protective gloves, protective clothing, eye and face protection.  
 P264: Wash skin thoroughly after handling.  
 P273: Avoid release to the environment.

### Response:

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
 P302+P352: IF ON SKIN: Wash with plenty of water  
 P332+P313: If skin irritation occurs: Get medical advice/attention.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337+P313: If eye irritation persists: Get medical advice/attention.  
 P308+P313: IF exposed or concerned: Get medical advice/ attention.

### Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

### Disposal:

P501: Dispose of contents and container in accordance with Federal, State and local regulations.

## EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** White Liquid, Styrene Odor.

**IMMEDIATE CONCERNS:** Flammable liquid and vapor. Vapors may travel to a source and flash back. May cause respiratory tract, eye and skin irritation.

## POTENTIAL HEALTH EFFECTS

**EYES:** Contact may cause eye irritation.

**SKIN:** May cause moderate to severe skin irritation. Prolonged exposure may cause skin burns.

**INGESTION:** May be harmful if swallowed. Symptoms include: gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration Hazard. Can cause chemical pneumonitis which can be fatal.

**INHALATION:** Breathing of high vapor concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Vapors expected to be slightly irritating.

**CARCINOGENICITY:** IARC: Classified 2B (possible for humans)

**ROUTES OF ENTRY:** Skin, Inhalation, Eyes

**TARGET ORGAN STATEMENT:** Liver, Central nervous system.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Styrene	20 - 30	100-42-5
Resin	20 - 30	N/A
Polymer	10 - 20	N/A
Talc	10 - 20	14807-96-6
Titanium Dioxide	10 - 20	13463-67-7

**COMMENTS:** The specific chemical identities are being withheld as a trade secret (29CFR1910.1200).

#### 4. FIRST AID MEASURES

**EYES:** Flush eyes with water for at least 15 minutes, holding eyelids open. Remove contact lenses if present and easy to do so. Seek immediate medical attention.

**SKIN:** Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**INGESTION:** Aspiration hazard. If swallowed, Do NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

**INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

**NOTES TO PHYSICIAN: Styrene:** Do not induce vomiting. Gastrointestinal decontamination in accidental petroleum distillate ingestions is not recommended, because of the severe aspiration hazard. Gastric lavage is indicated in those patients who require decontamination. Be sure that an endotracheal tube is in place prior to lavage; use cuffed tubes in patients over 7 years of age. All contaminated clothing should be removed, and contaminated skin areas washed with lipophilic soap, or green soap, and water. If ingested, cardiac and respiratory status must be continuously monitored. Be prepared to give oxygen and, if necessary, intubate. A chest x-ray should be taken immediately after stabilization of breathing and circulation to document aspiration and detect the presence of pneumothorax.

#### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Category 3 Flammable Liquid

**EXTINGUISHING MEDIA:** Small Fire: Water spray or fog, Alcohol-resistant foam, Dry chemical powder, carbon dioxide, sand or earth can be used for small fires.

Large Fire: Water spray or fog, Alcohol-resistant foam. Do not discharge extinguishing waters into the aquatic environment.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Formaldehyde vapors.

**EXPLOSION HAZARDS:** Vapours may form explosive mixture with air. Vapors are heavier than air and may spread along floors. Vapor may travel considerable distance to source of ignition and flash back.

**FIRE FIGHTING PROCEDURES:** Cool containers with flooding quantities of water until well after fire is out to avoid pressure build up, autoignition or explosion.

**FIRE FIGHTING EQUIPMENT:** Full Bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus (SCBA).

#### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Absorb with an inert material and put the spilled material in an appropriate waste disposal container.

**LARGE SPILL:** Flammable liquid. Keep away from heat and other sources of ignition. Eliminate all ignition sources. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into

sewers, basements or confined areas; dike if needed. Be careful that the product is not present at a concentration level above TLV.

## 7. HANDLING AND STORAGE

**HANDLING:** Use only in a well-ventilated area. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid direct contact (eye, skin, inhalation, ingestion) when possible. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Take precautionary measures against static discharges. Wash clothing before reuse. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.

**STORAGE:** Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Styrene	TWA	50		20	85
	STEL	100		40	170
Talc	TWA		2		2
Titanium Dioxide	TWA	[1]	10 [1]		10
<b>Footnotes:</b>					
1. Total Respirable Dust					

**ENGINEERING CONTROLS:** Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits (PEL/TLV). Any installed emergency eye wash station or safety showers should be located near the work area.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Chemical splash goggles. Always use proper eye protection around the work area.

**SKIN:** Wear solvent resistant gloves (consult safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**RESPIRATORY:** If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910. 134.

**WORK HYGIENIC PRACTICES:** Minimize exposure in accordance with good hygiene practice

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid.

**ODOR:** Solvent Odor.

**ODOR THRESHOLD:** No data available.

**APPEARANCE:** Colorless Liquid

**COLOR:** White.

**pH:** No data available.

**PERCENT VOLATILE:** No data available.

**FLASH POINT AND METHOD:** 28°C (83°F) Closed Cup

**FLAMMABLE LIMITS:** No data available.

**VAPOR PRESSURE:** No data available.

**VAPOR DENSITY:** No data available.

**BOILING POINT:** No data available.

**MELTING POINT:** No data available.

**POUR POINT:** No data available.

**SOLUBILITY IN WATER:** Negligible.

**EVAPORATION RATE:** No data available.

**SPECIFIC GRAVITY:** No data available.

**VISCOSITY:** No data available.

**(VOC):** No data available.

## 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes

**HAZARDOUS POLYMERIZATION:** Under normal conditions of use, hazardous reactions will not occur. Extreme heat can cause rapid, uncontrolled polymerization.

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Avoid contact with incompatible materials and ignition sources / heat.

**INCOMPATIBLE MATERIALS:** Avoid all unplanned contact with strong reactive chemicals, Acids, Bases, Aliphatic Amines, and Oxidizers.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Styrene	5000 mg / kg (Rat)	> 2000 mg / kg (dermal Rabbit)	11.8 mg/L (4h)
Titanium Dioxide	10000 mg / kg (Rat)		

**EYE EFFECTS:** Causes eye irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury.

**SKIN EFFECTS:** Skin irritant.

Prolonged or repeated exposure: may cause defatting of the skin, which can lead to dermatitis.

### CARCINOGENICITY

**IARC:** Group 2B - Possibly carcinogenic for humans.

**NTP:** Reasonably anticipated to be a human carcinogen

**OSHA:** Possible select carcinogen.

**Notes:** Listed by IARC as possibly carcinogenic to humans (Group 2B), based on limited evidence of carcinogenicity in humans and experimental animals.

**TARGET ORGANS:** Cardiac sensitization. Nervous system. Nasal cavity. Lung. Eye. Skin.

## 12. ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION:** Toxic to fish, invertebrates and microorganisms, however, substantial aquatic exposure is not expected based on the volatile nature of this material.

**BIOACCUMULATION/ACCUMULATION:** No data available.

**AQUATIC TOXICITY (ACUTE):** Acute toxicity to fish. Toxicity to aquatic plants.

**96-HOUR LC<sub>50</sub>:** 4-10 mg / L (Fathead Minnow)

**48-HOUR EC<sub>50</sub>:** 3-7 mg/L (Daphnia Magna)

**96-HOUR EC<sub>50</sub>:** 0.1-1. mg/L (Algae)

**Notes:** Information given is based on data on the components and the ecotoxicology of similar products.

**GENERAL COMMENTS:** No data is available on the product itself.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be in accordance with all Federal, State, and local regulations. Empty containers may still be considered dangerous due to residual vapors/liquid/dust.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Resin Solution

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** 1866

**PACKING GROUP:** III

**NAERG:** 127

### VESSEL (IMO/IMDG)

**SHIPPING NAME:** Resin Solution

**UN/NA NUMBER:** 1866

**PRIMARY HAZARD CLASS/DIVISION:** 3

**PACKING GROUP:** III

## 15. REGULATORY INFORMATION

### UNITED STATES

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**311/312 HAZARD CATEGORIES:** Fire Hazard, Immediate (acute) Health Hazard, Chronic (Delayed) Health Hazard, Reactivity.

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** Yes **ACUTE:** Yes **CHRONIC:** Yes

**313 REPORTABLE INGREDIENTS:** Styrene

**TITLE III NOTES:** Components meeting the requirements are listed.

**302/304 EMERGENCY PLANNING**

**EMERGENCY PLAN:** Not Listed.

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**

**CERCLA REGULATORY:** Styrene

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA REGULATORY:** All items are TSCA listed

**CLEAN AIR ACT**

**40 CFR PART 68---RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION:** Listed.

**CLEAN WATER ACT:** Listed.

**CANADA**

**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** Listed.

**WHMIS CLASS:** B2 Flammable Liquid, D2A Very Toxic Material, D2B Toxic Material.

**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components are listed.

**16. OTHER INFORMATION**


**PREPARED BY:** Fiberglass Coatings, Inc. (GS) **Date Revised:** 09/28/2015

**REVISION SUMMARY:** This MSDS replaces the 06/04/2014 MSDS. Revised: **Section 2:** .

**HMIS RATING**

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>3</b>
<b>PHYSICAL HAZARD</b>		<b>2</b>
<b>PERSONAL PROTECTION</b>		

**NFPA CODES**



**HMIS RATINGS NOTES:** The customer is responsible for determining the PPE code for this material.

**MANUFACTURER DISCLAIMER:** This information is compiled from sources believed reliable as of the date of issue, it is provided in good faith and correct to the best of our knowledge. No warranty, guarantee, or representation is made as to the sufficiency of the information for the safe use of the product nor to relieve the end user of their own Federal, State, and local regulatory compliance requirements.