

# SAFETY DATA SHEET



Date Issued : 7/9/2013  
MSDS No : 126179  
Date Revised : 9/11/2013  
Revision No : 1

## Gelcoat, White, Dusky, FCIWG-046, Gallon Can

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Gelcoat, White, Dusky, FCIWG-046, Gallon Can  
**PRODUCT CODE:** 126179

#### MANUFACTURER

Fiberglass Coatings Inc.  
www.fgci.com  
4301A 34th Street North  
St. Petersburg, FL 33714  
**Customer Service:** 800-272-7890  
**E-Mail:** fgci@fgci.com

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

Chem-Tel (800) 255-3924

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Skin Irritation, Category 2  
Acute Toxicity (Oral), Category 5  
Eye Irritation, Category 2A  
Aspiration Hazard, Category 1

##### Physical:

Flammable Liquids, Category 3

#### GHS LABEL



Flame



Exclamation  
mark



Health  
hazard

#### HAZARD STATEMENTS

H226: Flammable liquid and vapor.  
H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.

#### PRECAUTIONARY STATEMENT(S)

##### Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.../ equipment.  
 P233: Keep container tightly closed.  
 P240: Ground/bond container and receiving equipment.  
 P242: Use only non-sparking tools.  
 P243: Take precautionary measures against static discharge.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P264: Wash ... thoroughly after handling.

**Response:**

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P370+P378: In case of fire: Use ... to extinguish.  
 P337+P313: If eye irritation persists: Get medical advice/attention.  
 P301+A1600: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

**Storage:**

P403+P235: Store in a well-ventilated place. Keep cool.

**Disposal:**

P501: Dispose of contents/container in accordance with all Federal State and Local regulations

**EMERGENCY OVERVIEW**

**PHYSICAL APPEARANCE:** Liquid, Styrene Odor.

**IMMEDIATE CONCERNS: Flammable Liquid and Vapor.** Can cause eye and skin irritation. May contain some dust particles that could cause respiratory tract irritation. May contain traces of carcinogenic material. Avoid contact and exposure whenever possible.

**POTENTIAL HEALTH EFFECTS**

**EYES:** Can cause eye irritation. Symptoms include: stinging, tearing, redness, and swelling of the eyes.

**SKIN:** Can cause skin irritation. Symptoms may include redness, burning, drying and cracking of the skin, burns and other skin damage.

**INGESTION:** Swallowing can cause gastrointestinal irritation, nausea, diarrhea. Aspiration hazard. Aspiration can cause chemical pneumonitis, which can be fatal.

**INHALATION:** Vapors may contain dust that can cause increased respiratory tract irritation, lung irritation, headache, coughing, discomfort, etc.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

| Chemical Name                             | Vol. %  | CAS        |
|---|---------|------------|
| Styrene                                   | 30 - 40 | 100-42-5   |
| Polyester Resin (Trade Secret)            | 20 - 30 | XXXXXX     |
| Talc                                      | 10 - 20 | 14807-96-6 |
| Titanium Dioxide                          | 10 - 20 | 13463-67-7 |
| Unsaturated Polyester                     | 1 - 5   | 68511-26-2 |
| 2-propenoic Acid, 2-methyl-, Methyl Ester | 1 - 5   | 80-62-6    |

#### 4. FIRST AID MEASURES

**EYES:** Flush eyes for at least 15 minutes, holding eyelids open. If easily accomplished, check for and remove contact lenses. Seek immediate medical attention.

**SKIN:** Immediately flush with plenty of soap and water. Remove and dispose of contaminated clothing. Seek medical attention.

**INGESTION:** Aspiration hazard. If swallowed, Do NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

**INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

#### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Category 3 Flammable Liquid

**EXTINGUISHING MEDIA:** Use dry chemical, CO<sub>2</sub>, water spray/fog (not jet), or foam

**HAZARDOUS COMBUSTION PRODUCTS:** Ignition sources (and heat) can cause rapid, uncontrolled polymerization.

**EXPLOSION HAZARDS:** Vapors may form an explosive mixture with air.

**FIRE FIGHTING PROCEDURES:** Evacuate any non-essential personnel. Extinguish all ignition sources if safe to do so. Use water to cool exposed containers and structures until fire is out. Avoid spreading burning material with water used for cooling purposes.

**FIRE FIGHTING EQUIPMENT:** Full Bunker gear(helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus (SCBA).

#### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Extinguish all near by ignition sources. Stop leak if it can be done safely. Prevent from entering waterways and sewers. Absorb with non-combustible material and transfer into appropriate disposal container.

**LARGE SPILL:** Follow procedure for small spills. Dike ahead of spill to contain material. Water mist may be used to disperse vapors. Notify proper authorities if the spill cannot be contained. Follow Local, State, and Federal regulations for disposal.

**GENERAL PROCEDURES:** Always ensure proper ventilation from any spill. Respirators or SCBA are required if permissible exposure limits are exceeded due to inadequate general ventilation. All spills should be contained as best as possible. All chemical spills should be assumed to be hazardous to the environment to ensure safety.

#### 7. HANDLING AND STORAGE

**HANDLING:** Avoid ignition sources (flame, spark, smoking, etc) in use or handling areas. Use explosion proof electrical equipment. Ground all equipment containing this material. Do not ingest or breathe vapors/fumes. Avoid contact with eyes and skin. Always wear proper PPE when handling. Provide sufficient ventilation. A NIOSH respirator is required if permissible exposure limits are exceeded.

**STORAGE:** Store in a cool, dry, well-ventilated area, away from any sources of ignition and incompatible materials. Keep all equipment grounded to avoid static sparking. Keep container closed when not being used.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**EXPOSURE GUIDELINES**

| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200) |      |                 |                   |           |                   |
|---|------|-----------------|-------------------|-----------|-------------------|
|   |      | EXPOSURE LIMITS |                   |           |                   |
|   |      | OSHA PEL        |                   | ACGIH TLV |                   |
| Chemical Name                               |      | ppm             | mg/m <sup>3</sup> | ppm       | mg/m <sup>3</sup> |
| Styrene                                     | TWA  | 100             |                   | 20        | 85                |
|   | STEL |                 |                   | 40        | 170               |
| Talc  | TWA  |                 | 2                 |           | 2                 |
| Titanium Dioxide                            | TWA  | [1]             | 15 [1]            |           | 10                |
| 2-propenoic Acid, 2-methyl-, Methyl Ester   | TWA  | 100             | 410               | 50        | 205               |
|   | STEL |                 |                   | 100       | 410               |
| <b>Footnotes:</b>                           |      |                 |                   |           |                   |
| 1. Total Respirable Dust                    |      |                 |                   |           |                   |

**ENGINEERING CONTROLS:** Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits (PEL/TLV). Any installed emergency eye wash station or safety showers should be located near the work area.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Chemical splash goggles and/or face shield. Always use proper eye protection around the work area.

**SKIN:** Wear impermeable gloves. Clothing should limit skin exposure. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product. Maintain eyewash and shower station near work area in case of exposure.

**RESPIRATORY:** Vapor respirator may be required if exposure limits are exceeded. Use a NIOSH approved respirator or equivalent when required. Proper mechanical ventilation should be installed to ensure the exposure levels are below the allowable thresholds (PEL/TLV).

**WORK HYGIENIC PRACTICES:** Never eat or drink in areas where the chemical is being used. Wash hands after handling to limit exposure.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE:** Liquid

**ODOR:** Styrene Odor

**APPEARANCE:** Liquid, Color is dependent on color in name (variety of colors from clear to black) (Section 1: Trade Name)

**COLOR:** Varying color from colorless clear to black.

**PERCENT VOLATILE:** 49.86

**FLASH POINT AND METHOD:** 28.33°C (83°F) to 31.67°C (89°F) Closed Cup

**FLAMMABLE LIMITS:** 1% to 12.5%

**AUTOIGNITION TEMPERATURE:** 490°C (914°F)

**Notes:** Autoignition temp listed for Styrene (CAS: 100-42-5). Unknown autoignition for mixture.

**VAPOR PRESSURE:** 4.5 mm Hg @ 20 C

**BOILING POINT:** 100°C (212°F) to 145°C (293°F)

**SOLUBILITY IN WATER:** Insoluble.

**EVAPORATION RATE:** < 1 (Butyl Acetate = 1)

**SPECIFIC GRAVITY:** 1.27 (Water = 1)

**(VOC):** 39.040 %

## 10. STABILITY AND REACTIVITY

**STABLE:** Yes

**HAZARDOUS POLYMERIZATION:** Yes

**POLYMERIZATION:** Under normal conditions of use , hazardous reactions will not occur. Extreme heat can cause rapid, uncontrolled polymerization. Polymerization may also occur when contacted with amines (e.g. 2-part epoxy glue).

**CONDITIONS TO AVOID:** Avoid contact with incompatible materials and ignition sources / heat.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Extreme heat can cause rapid, uncontrolled polymerization.

**INCOMPATIBLE MATERIALS:** Avoid all unplanned contact with strong reactive chemicals, Acids, Bases, Aliphatic Amines, and Oxidizers.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE

| Chemical Name                             | ORAL LD <sub>50</sub><br>(rat) | DERMAL LD <sub>50</sub><br>(rabbit) | INHALATION<br>LC <sub>50</sub> (rat) |
|---|--------------------------------|-------------------------------------|--------------------------------------|
| Styrene                                   | 2650 mg / kg<br>(Rat)          |                                     | 12000 mg/m <sup>3</sup><br>(4h)      |
| 2-propenoic Acid, 2-methyl-, Methyl Ester | 7872 mg / kg<br>(Rat)          | > 5000 mg / kg                      | 5303 ppm<br>(inhalation/rat)<br>(4h) |

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** Environmental studies have not been performed for this mixture.

**ECOTOXICOLOGICAL INFORMATION:** Do NOT discharge into sewers or waterways. Numerical data is not available. Assumed to be toxic to aquatic life and the environment for safety.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be in accordance with all Local, State and Federal regulations. Empty containers may still be considered dangerous due to residual vapors/liquid/dust.

**RCRA HAZARD CLASS:** Waste Number: D001 (Ignitable)

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Resin Solution


**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** 1866

**PACKING GROUP:** III

**AIR (ICAO/IATA)****SHIPPING NAME:** Resin Solution**UN/NA NUMBER:** 1866**PRIMARY HAZARD CLASS/DIVISION:** 3**PACKING GROUP:** III**VESSEL (IMO/IMDG)****SHIPPING NAME:** Resin Solution**UN/NA NUMBER:** 1866**PRIMARY HAZARD CLASS/DIVISION:** 3**PACKING GROUP:** III**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** Fire Hazard, Immediate (acute) Health Hazard, Chronic (Delayed) Health Hazard, Reactivity.**TITLE III NOTES:** Components meeting the requirements are listed.**16. OTHER INFORMATION****PREPARED BY:** Fiberglass Coatings, Inc (HE)**REVISION SUMMARY:** This MSDS replaces the 7/10/2013 MSDS. Revised: **Section 8:** WORK HYGIENIC PRACTICES. **Section 14:** ADDITIONAL INFORMATION, AIR (ICAO/IATA) - SPECIAL PROVISIONS DOT (DEPARTMENT OF TRANSPORTATION) - NAERG ROAD AND RAIL (ADR/RID), ROAD AND RAIL (ADR/RID) ( VEHICLE FOR TANK, PROPER SHIPPING NAME, UN NUMBER, PACKING GROUP ), VESSEL (IMO/IMDG) ( PRIMARY HAZARD CLASS/DIVISION, PACKING GROUP, UN/NA NUMBER ).**HMIS RATING**

|                            |   |          |
|----------------------------|---|----------|
| <b>HEALTH</b>              | * | <b>2</b> |
| <b>FLAMMABILITY</b>        |   | <b>3</b> |
| <b>PHYSICAL HAZARD</b>     |   | <b>2</b> |
| <b>PERSONAL PROTECTION</b> |   | <b>J</b> |

**NFPA CODES****MANUFACTURER DISCLAIMER:** This information is compiled from sources believed reliable as of the date of issue, it is provided in good faith and correct to the best of our knowledge. No warranty, guarantee, or representation is made as to the sufficiency of the information for the safe use of the product nor to relieve the end user of their own Federal, State, and Local regulatory compliance requirements.